

PHACT™ CA8270P-B1

PHACT CA1270P-B1 is an environment-friendly semi-crystalline bio polymer which has excellent biodegradability. It is a compounded polymer with Polylactic acid and Amorphous polyhydroxyalkanoate. PHACT CA1270P-B1 is appropriate for blown film process to produce film applications.

PROPERTIES OF PHACT CA8270P-B1

Properties	Units	ASTM No	CA8270P-B1
Forms	-		Pellet
Specific Gravity	-	D792	1.23
Melting Point ¹⁾	°C	D3418	151.3
Glass Transition Temperature ¹⁾	°C	D3418	59.8
Melt Flow Rate (190°C, 2.16Kg)	g/10 min	D1238	4.6
Tensile Strength at Break ²⁾	MD		42
	TD		39
Elongation at Break ²⁾	MD	D882	300
	TD		300

1) Differential Scanning Calorimeter (DSC), peak of endotherm. Heating rate 10 °C/min.

2) Film specimens conforms to ASTM D882. Crosshead speed 200 mm/min for mechanical properties.

PROCESSING CONDITION FOR BLOW FILM

Dry Temperature ¹⁾	60 °C X 8 hrs	Feed Throat	20 ~ 40 °C
Feed Temperature	100 ~ 120 °C	Compression section	130 ~ 160 °C
Melt Temperature	130 ~ 160 °C	Nozzle	150 ~ 170 °C

1) It is preferable to dry with air below -40°C dew point.

CJ Biomaterials Inc. makes no warranty, express or implied, regarding the information contained herein or its products, including but not limited to any warranty as to the accuracy or completeness of information, or any implied warranty of merchantability or fitness for a particular purpose. The content of this document is subject to change without notice.