

Safety Data Sheet PHACT PHA resin

Section 1. Identification of the substance and the company/undertaking

1.1 Identification

Product name : PHACT PHA resin
Trade name : PHACT S1000P
CAS No. : 125495-90-1

1.2 Product use

Product use : Biopolymer (for industrial processing only)

1.3 Supplier

Supplier : CJ CHEILJEDANG CORPORATION
330, Dongho-ro, Jung-Gu, Seoul, Korea
Manufacturer : PT. CHEILJEDANG INDONESIA
Jl. Raya Arjosari Km. 9, Keamatan Rejoso,
Kabupaten Pasuruan, 67181 Jawa Timur,
Indonesia

1.4 Emergency telephone number : 82-31-8099-2323

Section 2. Hazards identification

2.1 Classification of the substance or mixture

GHS classification : Skin irritation, skin sensitization, eye irritation
(H315, H319).

2.2 GHS label elements

GHS labeling



2.3 Other hazards

Other hazards : No information available.

2.4 Potential health effects

: No information available.

Section 3. Composition/Information on ingredients

3.1 Substances

Substance type	Chemical name	CAS No.	Weight %
Polymers	Polyhydroxyalkanoate(P3HB4HB)	125495-90-1	> 98

Section 4. Human Health and Environmental Hazard Statements

4.1 Hazard and precautionary statements

Eye contact	: Immediately flush eyes with plenty of water for at least 15 minutes, lifting the upper and lower eyelids. Get medical aid.
Skin contact	: Wash off with soap and water.
Ingestion	: Get medical aid immediately. Do not induce vomiting without medical advice.
Inhalation	: Heating the resin above 200 ° C (392 ° F) during the process may result in strong characteristic odor of PHA. But it does not make any toxic fumes. Remove the victim from exposure area to fresh air immediately. Give oxygen if breathing is difficult. Get medical aid. Give artificial respiration if not breathing.

4.2 Notes to physician : Treat symptomatically.

Section 5. Firefighting measure

5.1 Flammability

Flash point	: 265 ° C.
Auto-ignition temp	: Not determined.

5.2 Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use water spray, dry chemical, carbon dioxide, or chemical foam.
Unsuitable extinguishing media	: None known.

5.3. Specific hazards arising from the chemical

Reactivity in case of fire	: Under fire conditions, hazardous fumes will be present: Carbon monoxide, Carbon dioxide.
-----------------------------------	--

5.4. Special protective equipment and precautions for fire-fighters

Protective equipment for firefighters	for : Wear a self-contained breathing apparatus in pressure-demand mode, MSHA/NIOSH (approved or equivalent), and full protective
--	--

gear.
Firefighting instructions : Evacuate personnel to a safe area. Use water spray for cooling exposed containers.

Section 6. Accidental release measures

6.1 Personal precautions

For non-emergency personnel : Wear recommended personal protective equipment. Evacuate unnecessary personnel. Ventilate spillage area. Avoid dust formation. Avoid contact with skin and eyes. Remove all sources of ignition.

For emergency responders : Do not attempt to take action without suitable protective equipment.

6.2 Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods for cleaning up : Sweep up and shovel into suitable containers for disposal.

Section 7. Handling and storage

7.1 Handling : Follow a good industrial practices in housekeeping and personal hygiene. Wear personal protective equipment. Maintain operating temperature within the recommended processing range. Avoid contact with molten material and provide adequate ventilation during processing. Keep only in original container. Protect from moisture. When mechanical energy is used to process or transfer, dust can be generated. Systems and procedures should be designed to minimize the generation and accumulation of dust from the handling and processing of PHA resin.

7.2 Storage : Avoid extremes of temperature and humidity to prevent property deterioration. Resin should be stored in original shipping package. Keep the resin dry and sealed to exclude moisture. Store below 30 °C (86 °F) to maximize product shelf life.

Section 8. Protection in the workplace

8.1 Control parameters

- Exposure limits** : Not established.
- Engineering controls** : Provide appropriate exhaust ventilation at places where the hot polymer may reside for long periods (leak areas, above the nozzle or die, in screen changers, in vent ports, etc.). Heating resin above recommended processing conditions will not produce fumes.

8.2 Personal protective equipment

- Eye protection** : Wear appropriate protective eyeglasses with side shields.
- Skin and body protection** : Personal protective equipment (“PPE”) must be selected and used in accordance with the Occupational Safety and Health Administration (OSHA)’s requirements at 29 C.F.R. § § 1910.132, 1910.133, and 1910.138. Wear impervious clothing and insulated gloves which provides a barrier of Liquids and Gases to prevent dermal exposure. Gloves must be replaced at the end of each work shift during which they are exposed to the New Chemical Substance.
- Respiratory protection** : Wear respiratory protection if there is potential for exposure to dust or fumes.

- 8.3 Other information** : Avoid contact with skin, eyes and clothing. Wash hands after handling the product. Use good housekeeping practices during storage, transfer, handling to avoid excessive dust accumulation.

Section 9. Physical and chemical properties

9.1 Information of physical and chemical properties

- Physical state** : Solid.
- Appearance** : pale yellow opaque pellets.
- Odor** : Mild.
- pH** : Not applicable.
- Melting Point** : 140–180 °C (284–356 °F).
- Freezing Point** : Not applicable.

Boiling Point	: Not applicable.
Flash Point	: 265 °C.
Evaporation rate	: Not determined.
Vapor Pressure	: Not determined.
Vapor Density	: Not determined.
Viscosity	: Not available.
Flammability	: Not available.
Density	: 1.1–1.3 g/cm ³
Solubility	: Soluble in chloroform, methylene chloride.
Partition coefficient	: Not determined.
Auto-ignition Temperature	: Not determined.
Decomposition Temperature	: > 275 °C (527 °F)
Molecular Weight	: Approximately >100,000 (by GPC)

Section 10. Stability and reactivity

10.1 Reactivity	: Non-reactive under normal conditions.
10.2 Chemical Stability	: Stable under recommended storage conditions.
10.3 Possibility of Hazardous Reaction	: Hazardous polymerization will not occur.
10.4 Conditions to Avoid	: High humidity environment.
10.5 Incompatible materials	: Strong oxidizing agents.
10.6 Hazardous Decomposition	: None under normal use conditions.

Section 11. Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: No information available.
Acute toxicity (dermal)	: No information available.
Acute toxicity (inhalation)	: No information available.
Skin corrosion/irritation	: No information available.
Serious eye damage/irritation	: No information available.
Respiratory or skin sensitization	: No information available.
Germ cell mutagenicity	: No information available.
Carcinogenicity	: No information available.
Reproductive toxicity	: No information available.
STOT-single exposure	: No information available.

STOT-repeated exposure : No information available.
Reproductive toxicity : No information available.

Section 12. Ecological information

12.1 Ecological Toxicity

: Not considered toxic in marine, fresh water, soil environment.

12.2 Persistence, degradability and bio-based products

:The product has the following certifications for biodegradability and bio-based products.

TUV AUSTRIA	: OK compost Industry : OK biodegradable Soil : OK compost Home : OK biodegradable Marine : OK biobased (Class4)
DIN CERTCO	: Industrial compostable products : DIN-Gepuft biobased
BPI	: Compostable product
USDA	: BioPreferred Program
JBPA	: Biodegradable Pla : Biomass Pla
12.3 Bioaccumulation	: Not expected to bioaccumulate.
12.4 Mobility in soil	: Inherently biodegradable in soil.

Section 13. Disposable considerations

13.1 Disposal methods

Waste treatment methods : There are no special requirements. In accordance with local and national regulations. Non-hazardous, biobased and biodegradable PHACT biopolymer resin is not designed to biodegrade in conventional landfills and is not part of the conventional plastics recycling stream.

Section 14. Transport information

14.1 Department of Transportation	: Not regulated.
14.2 Transportation of Dangerous Goods	: Not regulated.
14.3 IMDG	: Not regulated.

14.4 ICAO/IATA : Not regulated.

Section 15. Regulatory information

15.1 US regulations

TSCA List	: Listed (PMN completed)
Food contact Substance	: Listed FCN2330
SARA 313	: Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals required to be reported under this Act or Title 40, Code of Federal Regulations, Part 372
SARA 311/312 Hazard/Risk Category	
Acute Health Hazards	: None
Chronic Health Hazards	: None
Fire Hazards	: None
Sudden Pressure Release Hazard	: None
Reactive Hazards/Risks	: None

15.2 EU regulations

EU REACH	: Exemption
REACH Annex XVII	: Not Listed
REACH Candidate list	: Not Listed
REACH h Annex XIV (Authorization list)	: Not Listed
REACH Annex PIC list (EU 649/2012)	: Not Listed
REACH Annex POP list (EU 2019/1021)	: Not Listed
Other information, restriction and prohibition regulations	: No registration number is given for this substance because it is a polymer exempted from registration according to the provision of Article 2(9) of REACH
FCM Union list Annex I (EU 10/2011)	: Not Listed

15.3 China regulations

IECSC	: Listed
-------	----------

GB4806.6-2016	: Listed
15.4 Japan regulations	
ENCS	: Listed
FCM Positive list	: Not Listed
15.5 Korea regulations	
Korea REACH	: Exemption
Food Sanitation Act	: Listed
15.6 Other regulations	
DSL (Canada)	: Listed
NZioC (New Zealand)	: Not Listed(Compliant-certified exempt)
AICIS (Australia)	: Not Listed(Compliant-certified exempt)
TCSCA (Taiwan)	: PLC approval, Small quantity registration

Section 16. Other Information

16.1 Revision date	: 10/18/2024
16.2 Recommended restrictions	: None.

NOTICE: Customer assumes all risk with respect to its use and handling of this resin and its marketing, sale and use of products made with CJ CHEILJEDANG biopolymers. CJ CHEILJEDANG liability for branch of warranty, negligence, or other claims is limited to the purchase price of materials purchased. CJ CHEILJEDANG will not be responsible for any indirect, consequential, special, or incidental damages. The information contained herein is believed to be reliable, but CJ CHEILJEDANG makes NO REPRESENTATIONS,

PHACT

Revision Date: Oct. 18, 2024

Revision Number: 37

GUARANTEES, OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.